



QUOTE REQUEST - FRAMES

1075 HIALEAH DRIVE / HIALEAH, FL 33010-5551
Toll Free 1-888-605-3667 / Toll Free Fax 1-888-605-3539

Company Name _____ Date _____
Address _____ City _____ State _____ Zip _____
Contact Name _____ Email _____
Phone _____ Ext _____ Cell _____
Fax _____ Website _____

TAG # _____ **Quantity** _____ **1. Jamb Opening Size** _____ **2. Jamb Depth Dimension** _____
3. Throat Dimension _____ **4. Face Dimension** _____ **5. Head Dimension** _____

6. Elevation: Single Pair Side Light Double Light Transom Borrowed Light

7. Stainless Steel Type: 304 316
8. Gauge: 12 14 16
9. Finish: #2B (Paintable) #4 #6 #8 Other(Special) _____

10. Construction: Face Welded Full Throat Welded Knock Down
11. Profile: Double Rabbet Single Rabbet Cased Opening
12. Rating: None 20 Min. 45 Min. 60 Min. 90 Min. 180 Min. Label Construction (oversize)

13. Glazing Stops: Dual Flush Glaze Channel Stops Flush Glaze
14. Viewable: Viewable Opening Size _____
15. Glass: Thickness _____
 Tempered Laminate Wired Glass By Others Other _____

16. Anchors: Multi Purpose (Loose) Channel Type Welded-in Pierce and Dimple EWA Concealed EWA with Caps
 Masonry Loose "T" Anchors Adjustable Masonry No Anchors
 Compression Anchors

NOTE: (1) Fixed floor clips are standard for stud wall applications and new masonry applications. (2) Anchors bolts provided by others unless requested.

17. Hinge/Qty: 4 1/2" Std/Heavy _____
 5" Std/Heavy _____
 Cont. _____ Pivots _____
 Floor Closer _____ Elec. Hinge _____
 Other _____

18. Strike: 4 7/8" Strike 2 3/4" Deadbolt Strike Rim Exit
 Rim SVR Electric Strike CVR

19. Closer: Surface Mtd. (PA & Reg.) Automatic Operator
 Concealed Overhead Stop Reinforcement

Additional Comments/Sketch:

20. Preps: EPT Magnetic Lock Flush Bolt Surface Bolt Position Switch
 Sloped Sill Silencers Center Mullion Reinforcements DA Reinforcement

21. Special Conditions: _____

