



QUOTE REQUEST FRAMES

Company Name _____ Date _____
 Address _____ City _____ State _____ Zip _____
 Contact Name _____ Email _____
 Phone _____ Ext _____ Cell _____
 Fax _____ Website _____

1075 HIALEAH DRIVE / HIALEAH, FL 33010-5551
 Toll Free 1-888-605-3667 / Toll Free Fax 1-888-605-3539

TAG # _____ **Quantity** _____ **1. Jamb Opening Size** _____ **2. Jamb Depth Dimension** _____
3. Throat Dimension _____ **4. Face Dimension** _____ **5. Head Dimension** _____

6. Elevation: Single Pair Side Light Double Light Transom Borrowed Light

7. Stainless Steel Type: 304 316 **8. Gauge:** 12 14 16 **9. Finish:** #2B (Paintable) #4 #6 #8 Other(Special) _____

10. Construction: Face Welded Full Throat Welded Knock Down **11. Profile:** Double Rabbet Single Rabbet Cased Opening **12. Rating:** None 20 Min. 45 Min. 60 Min. 90 Min. 180 Min. Label Construction (oversize)

13. Glazing Stops: Dual Flush Glaze Channel Stops Flush Glaze **14. Viewable:** Viewable Opening Size _____ **15. Glass:** Thickness _____ Tempered Laminate Wired Glass By Others Other _____

16. Anchors: Multi Purpose (Loose) Channel Type Welded-in Pierce and Dimple EWA Concealed EWA with Caps Masonry Loose "T" Anchors Adjustable Masonry No Anchors Compression Anchors

NOTE: (1) Fixed floor clips are standard for stud wall applications and new masonry applications. (2) Anchors bolts provided by others unless requested.

17. Hinge/Qty: 4 1/2" Std/Heavy _____ 5" Std/Heavy _____ Cont. _____ Pivots _____ Floor Closer _____ Elec. Hinge _____ Other _____ **18. Strike:** 4 7/8" Strike 2 3/4" Deadbolt Strike Rim Exit Rim SVR Electric Strike CVR **19. Closer:** Surface Mtd. (PA & Reg.) Automatic Operator Concealed Overhead Stop Reinforcement

Additional Comments/Sketch:

20. Preps: EPT Magnetic Lock Flush Bolt Surface Bolt Position Switch Sloped Sill Silencers Center Mullion Reinforcements DA Reinforcement **21. Special Conditions:** _____